

## Hydraulic Series Scissor Lifts

**GTJZ0608(2132)**  
**GTJZ0808(2732)**  
**GTJZ0612(2146)**

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

### Product Highlights

#### Flexible operation

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot for efficient equipment transportation
- Folding guardrails for easy transport

#### Reduced maintenance costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- High quality parts and components

#### More reliable performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- The pothole protection reporting and horizontal protection system guarantee safety of operation

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Full-stroke operation
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic painting technology
■ 4×2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

# SINOBOOM

Sinoboom Intelligent Equipment

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park,  
Changsha, Hunan, China, 410600

🌐 [www.sinoboom.com](http://www.sinoboom.com)

✉ [sales@sinoboom.com](mailto:sales@sinoboom.com)

## Hydraulic Series Scissor Lifts

**GTJZ0608(2132)**  
**GTJZ0808(2732)**  
**GTJZ0612(2146)**

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

# SINOBOOM

Model	GTJZ0608(2132)	GTJZ0808(2732)	GTJZ0612(2146)
<b>Dimensions</b>			
Max Working Height	8.3m(27'3")	10.1m(33'2")	8.3m(27'3")
A Max Platform Height	6.3m(20'8")	8.1m(26'7")	6.3m(20'8")
B Max Horizontal Extension	0.9m(3')	0.9m(3')	0.9m(3')
C Length-Stowed	2.39m(7'10")	2.39m(7'10")	2.39m(7'10")
D Width-Stowed	0.8m(2'8")	0.81m(2'8")	1.15m(3'9")
Height-Stowed(Rail Folded)	1.83m(6')	1.96m(6'5")	1.6m(5'3")
E Height-Stowed(Rail Unfolded)	2.22m(7'3")	2.35m(7'9")	2.22m(7'3")
F Wheelbase	1.85m(6'1")	1.85m(6'1")	1.85m(6'1")
Ground Clearance	0.1m(4")	0.1m(4")	0.1m(4")
Platform Dimensions(L×W×H)	2.25m×0.81m×1.1m (7'5"×2'8"×3'7")	2.25m×0.81m×1.1m (7'5"×2'8"×3'7")	2.25m×1.15m×1.1m (7'5"×3'9"×3'7")
<b>Performance</b>			
Platform Allowable Occupants (Indoor/Outdoor)	2 persons/1 person	2 persons/-	2 persons
Platform Capacity	380kg(838lbs)	250kg(551lbs)	550kg(1,213lbs)
Drive Speed-Stowed	3.2km/h(2mph)	3.2km/h(2mph)	3.2km/h(2mph)
Drive Speed-Raised	0.8km/h(0.5mph)	0.8km/h(0.5mph)	0.8km/h(0.5mph)
Elevation Time(Unloaded)	25s~30s	30s~35s	33s~38s
Descent Time(Unloaded)	30s~35s	34s~39s	30s~35s
Turning Radius(Inside/Outside)	0/2.1m(0/6'11")	0/2.1m(0/6'11")	0/2.35m(0/7'9")
Tilt Rating (Front to Back/Side to Side)	3°/1.5°	3°/1.5°	3°/1.5°
Tyre Size/Type	380×125mm (15×5")/solid	380×125mm (15×5")/solid	380×125mm (15×5")/solid
<b>Power</b>			
Batteries	6V×4/225Ah	6V×4/225Ah	6V×4/240Ah
Power Source	24V DC	24V DC	24V DC
Drive Mode	2WD, front-wheel	2WD, front-wheel	2WD, front-wheel
Charger Input	100~240V AC	100~240V AC	100~240V AC
Charger Output	30A	30A	30A
Brake	2 rear wheel	2 rear wheel	2 rear wheel
Hydraulic System Capacity	16L(3.5gal)	16L(3.5gal)	20L(4.4gal)
<b>Weight</b>			
Weight	1,770kg(3,903lbs)	1,970kg(4,344lbs)	2,070kg(4,564lbs)
Standards Compliance	ISO/CE/ANSI/CSA/AS/CU-TR/KCS		

