

ROUGH TERRAIN SCISSOR LIFTS

GTJZ1323RH(4389RH) /GTJZ1623RH(5389RH)

Compliance with ISO/CE/ANSI standards

PRODUCT HIGHLIGHTS

Excellent performance

- Powerful platform capacity for unprecedented efficiency
- Two-way extendable platform, spacious working platform
- Wide-angle tilt, one-click outrigger leveling

Strong off-road performance

- Stable movement, copes well with potholed ground.

Easy maintenance

- Integrated pipeline assembly, convenient for troubleshooting
- Double-door design for easy maintenance, spacious area for maintenance
- Drawer-type engine compartment, easy maintenance

Green

- Comfortable working environment without noise pollution
- Meet indoor or emissions-critical site requirements.Economical

Economical

- Range anxiety free with engine driven generator, providing continue power

Standard features		
4WDx2WS	Fault diagnosis system	Maintenance-free battery
Oscillating system	Tilt protection system	Raised traveling
Auto braking system	Emergency stop buttons	Overload sensing system
Optional features		
AC power cable to platform	Platform work light	Overhead anti-collision device
Non-marking tyres	Headlight	

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ROUGH TERRAIN SCISSOR LIFTS

GTJZ1323RH(4389RH) /GTJZ1623RH(5389RH)

Compliance with ISO/CE/ANSI standards

Model	GTJZ1323RH(4389RH)	GTJZ1623RH(5389RH)
Dimensions		
Max Working Height	15.1m(49'7")	18.2m(59'9")
A Max Platform Height	13.1m(43')	16.2m(53'2")
B Max Horizontal Extension	1.5m/1.2m(4'11"/3'11")	1.5m/1.2m(4'11"/3'11")
C Length-Stowed	4.88m(16')	4.88m(16')
D Width-Stowed	2.28m(7'6")	2.28m(7'6")
E Height-stowed (Rail Unfolded)	2.22m(7'3")	2.44m(8')
E Height-stowed (Rail Unfolded)	2.98m(9'9")	3.21m(10'6")
F Wheelbase	2.84m(9'4")	2.84m(9'4")
Ground Clearance	0.36m(1' 2")	0.36m(12")
Platform Dimensions(LxWxH)	3.98mx1.83mx1.1m(13'x6'x3'7")	3.96mx1.83mx1.1m(13'x6'x3'7")
Extension Platform Length	6.68m(21'10")	6.68m(21'10")
Performance		
Platform Allowable Occupants (Indoor/Outdoor)	4 Persons/4 Persons	4 Persons/4 Persons
Platform Capacity	680kg(1,499lbs)	680kg(1,499lbs)
Drive Speed-Stowed	5.3km/h(3.3mph)	5.3km/h(3.3mph)
Drive Speed-Raised	1.1km/h(0.68mph)	1.1km/h(0.68mph)
Elevation Time(Unloaded)	60s~80s	70s~90s
Descent Time(Unloaded)	50s~60s	60s~70s
Gradeability	50%	40%
Turning Radius(Inside/Outside)	2.2m/5.3m(7'3"/17'5")	2.2m/5.3m(7'3"/17'5")
Tilt Rating(Front to Back)	3°	3°
Tilt Rating(Side to Side, Outrigger Tele-In/ Tele-Out)	2°/0.8°	2°/0.8°
Max Outrigger Leveling(Front to back)	7°	7°
Max Outrigger Leveling(Side to side)	12°	12°
Tire Spec/Type	33x12-20/solid	33x12-20/solid
Power		
Engine	Yanmar 4.4kW Stage V Yanmar 4.8kW EPA Tier 4	Yanmar 4.4kW Stage V Yanmar 4.8kW EPA Tier 4
Batteries	2x24 V,480 Ah	2x24 V,480 Ah
Drive Mode	4WDx2WS	4WDx2WS
Fuel Tank Capacity-Diesel	3.3L(0.22 gal(UK)/0.26 gal(US))	3.3L(0.22 gal(UK)/0.26 gal(US))
Hydraulic Tank Capacity	110L(24 gal(UK)/29 gal(US))	110L(24 gal(UK)/29 gal(US))
Weight		
Weight(Outriggers/ Without Outriggers)	8,560kg(18,871lbs)	9,330kg(20,569lbs)
Standards Compliance		ISO/CE/ANSI

